



NUTRIENT CONTROL ADDITIVE FOR ANHYDROUS AMMONIA & MANURES

ACTIVE INGREDIENTS..... 10%

COMPLEXED CALCIUM NANO-PARTICLES

INERT INGREDIENTS..... 90%

PROPRIETARY MIXTURE OF PROPYLENE GLYCOL, POLYMERS AND OTHER INERT INGREDIENTS


**PLEASE READ CAREFULLY BEFORE USING - KEEP OUT OF THE REACH OF CHILDREN
SHAKE WELL BEFORE USE - STORE ABOVE 32°F - HARMFUL IF SWALLOWED**

GENERAL INFORMATION:

CAPTIS IS A NUTRIENT CONTROL ADDITIVE THAT IMPROVES SOIL RETENTION AND PLANT UPTAKE OF NITROGEN, AS WELL AS REDUCING NITROGEN LOSS. CAPTIS IS INTENDED TO BE USED TO ENHANCE SOIL CHEMISTRY FOR RETAINING ANHYDROUS AMMONIA, AND LIQUID MANURES, AND TO BE USED AS A SUPPLEMENT TO A REGULAR FERTILIZER PROGRAM. THIS PRODUCT IS NOT PLANT FOOD AND IS NOT INTENDED FOR USE AS A FERTILIZER.

WARNING:

USE ONLY ACCORDING TO LABEL DIRECTIONS AND AT RECOMMENDED RATES. ALWAYS WEAR PROPER PERSONAL PROTECTION INCLUDING LONG SLEEVES, LONG PANTS, GOGGLES, AND CHEMICAL RESISTANT GLOVES WHEN HANDLING THIS PRODUCT. USE ONLY WITH ADEQUATE VENTILATION. IF ORGANIC VAPORS OR DUSTS ARE PRESENT ABOVE THEIR REGULATORY LIMITS, FOLLOW A RESPIRATORY PROTECTION PROGRAM WHENEVER WORKPLACE CONDITIONS WARRANT RESPIRATOR USE.

WARNING	
	<p>H315: CAUSES SKIN IRRITATION. H318: CAUSES SERIOUS EYE DAMAGE. H335: MAY CAUSE RESPIRATORY IRRITATION. H360: MAY DAMAGE FERTILITY OR THE UNBORN CHILD. P260: DO NOT BREATHE VAPORS/SPRAY. P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. P280: WEAR FACE PROTECTION, PROTECTIVE CLOTHING, PROTECTIVE GLOVES. P305+P351+P338+P310: IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES IF PRESENT AND EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A DOCTOR OR POISON CENTER. P308 + P313: IF EXPOSED OR CONCERNED, SEEK MEDICAL ADVICE/ATTENTION. P405: STORE IN A SECURE LOCATION.</p>



GENERAL USE RATES:

- 6 OZ PER 50 UNITS OF NITROGEN
- 6 QTS PER TON OF ANHYDROUS AMMONIA
- 24-32 OZ PER ACRE FOR LIQUID MANURE

DIRECTIONS FOR USE:

ANHYDROUS AMMONIA

1. OPERATOR MUST FOLLOW ALL ANHYDROUS AMMONIA SAFETY PRECAUTIONS
2. INJECT CAPTIS THROUGH LIQUID FILL VALVE
3. IF PRESSURE EXCEEDS 150 PSI, INJECT CAPTIS THROUGH THE LIQUID WITHDRAW VALVE
4. PROPER MAINTENANCE IS REQUIRED. FLUSH VALVE THOROUGHLY WITH ANHYDROUS. COAT FILL VALVE THOROUGHLY WITH PETROLEUM OR SILICONE BASED LUBRICANT
5. APPLY TREATED ANHYDROUS USING CONVENTIONAL ANHYDROUS APPLICATION EQUIPMENT

MANURES

CAPTIS MAY BE MIXED WITH LIQUID ANIMAL MANURES. CAPTIS MAY BE APPLIED TO SLURRY PIT OR THROUGH AN INJECTION SYSTEM AS MATERIAL IS LOADED INTO THE APPLICATOR.

ANHYDROUS AMMONIA CONSIDERATIONS: THOROUGHLY CLEAN ALL PARTS, PUMPS AND EQUIPMENT BEFORE USE OF CAPTIS. PRODUCT CAN LOOSEN BUILDUP ON PUMP EQUIPMENT AND TANKS THAT CAN CAUSE THE DEBRIS TO CLOG TOOL BARS AND INJECTION EQUIPMENT. CAPTIS MAY BE PUMPED INTO THE ANHYDROUS TANK THROUGH THE LIQUID FILL VALVE BEFORE, DURING, OR AFTER LOADING. IT IS BEST TO FILL TANK HALFWAY THEN INJECT ALL CAPTIS AND FINISH FILLING. TANK CAN HEAT UP, ESPECIALLY IN HOT WEATHER. PUMPING AND METERING SYSTEMS ARE NECESSARY FOR THE INJECTION OF CAPTIS INTO THE TANK. CAPTIS IS THEN APPLIED TO CROPLAND USING CONVENTIONAL AMMONIA APPLICATION EQUIPMENT. TANK MIXING WITH ANHYDROUS AMMONIA IS THE MOST COMMONLY USED METHOD OF APPLICATION; HOWEVER, CAPTIS MAY ALSO BE APPLIED THROUGH DOWNSTREAM INJECTION SYSTEMS.

STORAGE AND HANDLING: CAPTIS SHOULD BE STORED IN A TEMPERATURE RANGE OF 32°-100°F. STORE IN ORIGINAL CONTAINER ONLY. KEEP PACKAGES TIGHTLY CLOSED AND DO NOT ALLOW WATER TO BE INTRODUCED TO THE CONTAINER. DO NOT STORE NEAR HEAT OR AN OPEN FLAME. EXPOSURE OF CAPTIS TO BELOW FREEZING TEMPERATURES FOR AN EXTENDED PERIOD MAY RESULT IN THE FORMATION OF GEL AND/OR CRYSTALS. IF THIS OCCURS, EXPOSE THE PRODUCT TO AMBIENT TEMPERATURES GREATER THAN 55°F. THIS WILL RESULT IN RECONSTITUTION OF THE PRODUCT, WITH NO DEGRADATION OF THE ACTIVE INGREDIENT.

CONDITIONS OF SALE-LIMITED WARRANTY AND LIMITATIONS OF LIABILITY AND REMEDIES: IF THESE TERMS ARE NOT ACCEPTABLE, RETURN THE PRODUCT, UNOPENED, AND THE FULL PURCHASE PRICE WILL BE REFUNDED. THIS LABEL IS BELIEVED TO BE RELIABLE AND MUST BE FOLLOWED CAREFULLY. INJURY TO CROPS, ANIMALS, HUMANS, OR THE ENVIRONMENT WHERE THE PRODUCT HAS BEEN APPLIED MAY RESULT FROM EXTRAORDINARY OR UNUSUAL WEATHER CONDITIONS, FAILURE TO FOLLOW THE LABEL DIRECTIONS, OR POOR APPLICATION PRACTICES, ALL OF WHICH ARE BEYOND THE CONTROL OF THE MANUFACTURER AND THE SELLER. THE MANUFACTURER WARRANTS THAT THIS PRODUCT CONFORMS TO THE CHEMICAL DESCRIPTION ON THE LABEL AND IS REASONABLY FIT FOR THE PURPOSE REFERRED TO. THE MANUFACTURER MAKES NO OTHER WARRANTIES OR REPRESENTATIONS OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT, INCLUDING NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, AND NO SUCH WARRANTY SHALL BE IMPLIED BY LAW. THE EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OR SELLER FOR ANY CAUSE OF ACTION RELATING TO THE HANDLING OR USE OF THIS PRODUCT SHALL BE LIMITED TO, AT THE SELLER'S CHOICE, ONE OF THE FOLLOWING: 1. REFUND OF THE PURCHASE PRICE, OR 2. REPLACEMENT OF THE PRODUCT USED. NEITHER THE MANUFACTURER NOR THE SELLER SHALL BE LIABLE FOR ALL CLAIMS AGAINST THE COMPANY THAT ARE WAIVED FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OR EXPENSE OF ANY NATURE, INCLUDING, BUT NOT LIMITED TO, LOSS OF PROFITS OR INCOME BY THE END USER. THE MANUFACTURER AND THE SELLER OFFER THIS PRODUCT AND THE BUYER AND USER ACCEPT IT, SUBJECT TO THE FOREGOING CONDITIONS OF SALE AND LIMITATION OF WARRANTY, LIABILITY AND REMEDIES.

WEIGHT PER GALLON

12 lbs.

NET CONTENT

250 Gal | 3,000 lbs.

MANUFACTURED BY TIMAC AGRO USA
 P.O. Box 888 - ROUTE 724 & I-176 READING, PA
 19607 -0888 - USA

